



ODISMATIC® Self-cleaning screen filters

Municipality

Industry

Irrigation

HYDRAULIC FILTERS €€

ELECTRIC FILTERS €€

- New design suction nozzles reduce water consumption during flushing
- Reversible bidirectional unit for efficient cleaning mechanism



8, Martin Gehl St., P.O.B. 3137, Kiryat-Arye, Petach-Tikva 4951257, Israel • Tel.: 972-3-9258503 • Fax.: 972-3-9214515

E-mail: odis@odisfiltering.com Visit us at • <http://www.odisfiltering.com>

Copyright © 2015, By ODIS Filtering Ltd., All Rights Reserved.

OdisMatic® Hydraulic Self-cleaning screen filters:

Series	Description
OMH71	Compact filter. Inlet sizes Available: 3/4", 1", 1 1/2", 2", 3", 4", 6", 8", 10" Flow rate : 4m³/h-400m³/h
OMH72®	Especially designed for high flow rates and high load of dirt. Inlet sizes Available: 12", 14", 16", 18", 20" Flow rate : 600m³/h - 1600m³/h
OMH73®	Compact filter for high load of dirt. Inlet sizes Available: 2", 3", 4", 6", 8", 10", 12", 14" Flow rate : 25m³/h - 550m³/h



OdisMatic® ELECTRIC Self-cleaning screen filters:

Series	Description
OME82®	Especially designed for high flow rates and high load of dirt. Inlet sizes Available: 12", 14", 16", 18", 20" Flow rate : 600m³/h - 1600m³/h
OME83®	Compact filter for high load of dirt. Inlet sizes Available: 2, 3", 4", 6", 8", 10", 12", 14" Flow rate : 25m³/h - 550m³/h

